

(12)

(21) 2 430 181

(51) Int. Cl. 7: **G06F 19/00, G06F 17/00,
G07F 9/00, G06F 17/40**

(22) 27.05.2003

(71) **CSTAR TECHNOLOGIES INC.,**
1-1122 Finch Avenue., WEST TORONTO, O1 (CA).

COVELEY, MICHAEL E. (CA).


(74) **SIM & MCBURNEY**

(72)

(54) **SYSTEME ET METHODE DE SUIVI DES STOCKS**
(54) **SYSTEM AND METHOD FOR TRACKING INVENTORY**

(57)

An inventory-tracking unit associated with a storage unit holding items to be dispensed includes a card reader to read an access card issued to a user and a scanner to scan data from items removed from the storage unit. A processor communicates with a sensor in the storage unit and with the card reader and scanner. The sensor provides item data to the processor that is associated with items removed from the storage unit. The processor compares item data received from the sensor with the data received from the scanner to detect coincidence. The processor generates a transaction upon coincidence of item data received from the sensor with the scanned data. A communications interface transmits the transaction to a remote site.





Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2430181 A1 2004/11/27

(21) 2 430 181

(12) DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION

(13) A1

(22) Date de dépôt/Filing Date: 2003/05/27

(41) Mise à la disp. pub./Open to Public Insp.: 2004/11/27

(51) Cl.Int.⁷/Int.Cl.⁷ G06F 19/00, G06F 17/40, G07F 9/00,
G06F 17/00


(71) Demandeur/Applicant:
CSTAR TECHNOLOGIES INC., CA

(72) Inventeur/Inventor:
COVELEY, MICHAEL E., CA

(74) Agent: SIM & MCBURNEY

(54) Titre : SYSTEME ET METHODE DE SUIVI DES STOCKS

(54) Title: SYSTEM AND METHOD FOR TRACKING INVENTORY



(57) Abrégé/Abstract:

An inventory-tracking unit associated with a storage unit holding items to be dispensed includes a card reader to read an access card issued to a user and a scanner to scan data from items removed from the storage unit. A processor communicates with a sensor in the storage unit and with the card reader and scanner. The sensor provides item data to the processor that is associated

Canada

<http://opic.gc.ca> • Ottawa-Hull K1A 0C9 • <http://cipo.gc.ca>

OPIC • CIPO 191

OPIC



CIPO

(57) Abrégé(suite)/Abstract(continued):

with items removed from the storage emit. The processor compares item data received from the sensor with the data received from the scanner to detect coincidence. The processor generates a transaction upon coincidence of item data received from the sensor with the scanned data. A communications interface transmits the transaction to a remote site.

ABSTRACT

An inventory-tracking unit associated with a storage unit holding items to be dispensed includes a card reader to read an access card issued to a user and a
5 scanner to scan data from items removed from the storage unit. A processor communicates with a sensor in the storage unit and with the card reader and scanner. The sensor provides item data to the processor that is associated with items removed from the storage unit. The processor compares item data received from the sensor with the data received from the scanner to detect coincidence. The processor
10 generates a transaction upon coincidence of item data received from the sensor with the scanned data. A communications interface transmits the transaction to a remote site.

SYSTEM AND METHOD FOR TRACKING INVENTORY

Field of the Invention

The present invention relates generally to inventory management and in particular to a system and method for tracking inventory and to an inventory-tracking unit.

5

Background of the Invention

Inventory control is a primary concern for product retailers so that excess and insufficient inventory situations are avoided. Within a mortar and bricks environment, inventory is controlled by counting existing inventory at physical locations. Controlling inventory in this manner is however much more difficult and in fact impractical in environments where inventory is dispensed through stocked vending machines that are distributed over a large geographical area.

To deal with inventory control in these environments, service personnel are dispatched along service routes according to pre-set schedules so that the vending machines can be checked for inventory levels and proper operation. As will be appreciated, during a service route all vending machines along the service route are checked. In many instances, the checks reveal that the vending machines are operating properly and hold sufficient inventory. As a result, the checks are unnecessary. In other instances, the checks reveal that the vending machines have malfunctioned and/or are depleted of inventory, resulting in potential lost sales especially if delays exist between checks.

A similar problem exists in the medical supply environment where medical, surgical, biological and/or pharmaceutical supplies are stored in refrigeration units distributed throughout medical, research and/or educational facilities located at different geographical locations. In the past, dispatching medical supplies through these refrigeration units has been based on the honor system. Users removing supplies from refrigeration units are expected to list the removed supplies on charts posted on the refrigeration units so that supply usage can be tracked and costs assigned in the appropriate manner.

As will be appreciated, inventory control in this medical supply environment suffers similar problems to those encountered in the vending machine environment discussed above. Routine checks of all refrigeration units must be

30

- 2 -

carried out to determine the inventory level and operating status of the refrigeration units. In many cases the checks are either unnecessary or late. The latter condition can be particularly problematic in the case where a refrigeration unit fails and the temperature within the refrigeration unit rises to a point where the inventory is
5 spoiled. Inventory shrinkage is also a problem in the medical supply environment. In many instances, users removing supplies from the refrigeration units fail to record accurately the removed items. As a result, costs for the missing inventory cannot be assigned. As will be appreciated, improvements in inventory control in these types of environments are desired.

10 It is therefore an object of the present invention to provide a novel system and method for tracking inventory and a novel inventory-tracking unit.

Summary of the Invention

According to one aspect of the present invention there is provided an
15 inventory-tracking unit associated with a storage unit holding items to be dispensed comprising:

a card reader to read an access card issued to a user;
a scanner to scan data from items removed from said storage unit;
a processor communicating with a sensor in said storage unit and with
20 said card reader and scanner, said sensor providing item data to said processor that is associated with items removed from said storage unit, said processor comparing item data received from said sensor with data received from said scanner to detect coincidence, said processor generating a transaction upon coincidence of item data received from said sensor with said scanned data; and
25 a communications interface to transmit said transaction to a remote site.

In the preferred embodiment, the communications interface transmits the transaction over a wireless communications link, the scanner is a barcode scanner, the card reader is designed to read a magnetic stripe on an access card and the storage
30 unit is a refrigeration unit. A housing accommodates the card reader, scanner, processor and communications interface. The housing is coupled to the storage unit and the processor is wired to the sensor. During access of the storage unit, the card

- 3 -

reader locks the access card therein until the item data received from the sensor is coincident with the read data.

In one embodiment, the inventory-tracking further comprising a locking mechanism coupled to the storage unit to inhibit access to items held therein.

5 The locking mechanism is conditioned by the processor to a disengaged state to permit access to items held in the storage unit when a valid access card is read by the card reader. The processor communicates with at least one diagnostic sensor associated with the storage unit and transmits an alarm event to the remote site in response to alarm condition input received from the at least one diagnostic sensor.

10 The present invention provides advantages in that the inventory-tracking unit can be easily retrofitted to existing refrigeration units thereby to permit existing refrigeration units to be upgraded so that inventory therein can be remotely monitored and tracked over a wireless communications link. Since the inventory-tracking unit controls access to the inventory within the refrigeration unit, distribution
15 of restricted inventory can be accurately controlled thereby inhibiting inventory loss through inventory expiry and/or shrinkage.

The present invention also provides advantages in that since inventory removed from the refrigeration unit is tracked in real time, inventory within the refrigeration unit can be managed to avoid item "sell-out" conditions. Statistical
20 information concerning inventory use can also be easily generated allowing inventory stocking procedures to be adjusted to meet inventory demand. In addition, if the refrigeration device suffers a failure and the temperature within the refrigeration unit rises above a threshold temperature, since the operating state of the refrigeration unit is remotely monitored service personnel can be dispatched quickly to avoid inventory
25 spoilage.

Brief Description of the Drawings

Embodiments of the present invention will now be described more fully with reference to the accompanying drawings in which:

30 Figure 1 is a front elevation view of a refrigeration unit in combination with an inventory-tracking unit in accordance with the present invention;

- 4 -

Figure 2 is a front elevation view of the inventory-tracking unit of Figure 1;

Figure 3 is a left side elevation view of the inventory-tracking unit of Figure 1;

5 Figure 4 is a right side elevation view of the inventory-tracking unit of Figure 1;

Figure 5 is a rear elevation view of the inventory-tracking unit of Figure 1;

Figure 6 is a top plan view of the inventory-tracking unit of Figure 1;

10 Figure 7 is a front elevation view of the interior of the inventory-tracking unit of Figure 1;

Figure 8 is a block diagram of the internal circuitry within the inventory-tracking unit of Figure 1;

15 Figure 9 is a flowchart showing the steps performed by the inventory-tracking unit during accessing of the refrigeration unit;

Figure 10 is a schematic view of an inventory-tracking system including an inventory-tracking unit that communicates with a remote site over a wireless wide area network;

20 Figure 11 is a front elevation view of a refrigeration unit in combination with a top mounted inventory-tracking unit; and

Figure 12 is a schematic view of an inventory-tracking system including inventory-tracking units that communicate with a computer room over a wireless local area network.

25 **Detailed Description of the Preferred Embodiments**

Turning now to Figure 1, a refrigeration unit such as a freezer in which medical, surgical, biological and/or pharmaceutical supplies (hereinafter referred to as "medical supplies") are stored, is shown and is generally identified by reference numeral 20. An inventory-tracking unit 30 is coupled to one side of the refrigeration unit 20 to track inventory removed from the refrigeration unit. The inventory-tracking unit 30 may alternatively be mounted on the top of the refrigeration unit 20 as shown in Figure 11.

- 5 -

The refrigeration unit 20 for the most part is standard and receives power from a conventional 120 volt AC power source via an electrical cord. A door light switch is provided in the refrigeration unit 20 to sense when the door of the refrigeration unit is in an open or closed condition. As is known, when the door of the refrigeration unit 20 is opened, the door light switch closes a circuit causing an internal light within the refrigeration unit 20 to illuminate. An internal sensor antenna of the acoustic or electromagnetic type is accommodated within the rubber seal surrounding the door frame of the refrigeration unit 20 to sense tagged items being placed in or removed from the refrigeration unit. A temperature sensor in the form of a thermistor is also provided in the refrigeration unit 20 to sense when the temperature within the refrigeration unit 20 rises above a threshold temperature.

Figures 2 to 6 better illustrate the physical layout of the inventory-tracking unit 30. As can be seen inventory-tracking unit 30 includes a housing 32 that is secured to the side of the refrigeration unit 20 by a plurality of suitable fasteners (not shown). The front face of the housing includes a barcode reader 34, a display 36 and a card reader 38. A spring-loaded solenoid door lock 40 is also provided on the front face and is actuatable to engage and disengage the door of the refrigeration unit to control entry into the refrigeration unit 20. An antenna 42 is provided on one side of the housing 32 to allow the inventory-tracking unit 30 to communicate with a remote site over a wireless communication link as will be described. Ventilation-holes 44 are provided in the top of the housing 32 to allow air to circulate within the housing 32 thereby to dissipate heat.

Turning now to Figure 7, the integrated internal physical layout of the inventory-tracking device 30 is illustrated. The inventory-tracking device 30 includes the card reader 38 and the solenoid door lock 40. The barcode reader 34, the display 36, communicates with a modem 52 that is coupled to the antenna 42 as well as with a multi-drop bus (MDB) board 54. An audio siren 56 is also coupled to the main control board 50.

The circuitry on the main control board 50 and the multi-drop bus board 54 is illustrated in Figure 8 and is generally identified by reference numeral 60. As can be seen, circuitry 60 includes a central processing unit (CPU) 62 having a real-

- 6 -

time clock. CPU 62 communicates with a microprocessor supervisor 64 and with a plurality of interfaces via a databus 66, namely a card reader interface 68, a radio interface 70, and a freezer interface 72. Card reader interface 68 is coupled to the card reader 38. Radio interface 70 is coupled to a wide area network (WAN) radio transceiver 74 and/or to a local area network (LAN) radio transceiver 76. The transceivers 74 and 76 communicate with the antenna 42 thereby to permit wireless communications. The freezer interface 72 is coupled to the solenoid door lock 40.

CPU 62 further communicates with static random access memory (RAM) 80, flash memory 82 and communications interface 84 via the databus 66. The communications interface 84 communicates with the internal sensor antenna within the refrigeration unit 20. The display 36 is also coupled to the databus 66 and communicates with the CPU 62. An on-board power supply 86 provides the necessary power for operation of the inventory-tracking unit 30. On-board power supply 86 is coupled to the electrical cord of the refrigeration unit 20 via an interconnecting harness (not shown). CPU 62 also receives conductors coupled to the door light switch within the refrigeration unit 20 via the interconnecting harness allowing a time stamp to be generated when the door of the refrigeration unit 20 is opened and then closed.

The operation of the inventory-tracking unit 30 will now be described with particular reference to Figure 9. When a user wishes to gain access to the refrigeration unit 20, the user inserts their access card into the card reader 38. When the card reader 38 detects the inserted card (step 202), the magnetic stripe on the access card is read (step 204) and the read card data is conveyed to the CPU 62 via the databus 66. The CPU 66 in turn compares the read card data with a list of authorized users to determine if the card is valid (step 206). If the read card data is determined to be invalid, the user is denied access to the refrigeration unit 20. The access card is ejected from the card reader 38 (step 208) and the card reader returns to a ready state waiting for another access card to be inserted therein (step 200). At step 206, if the read card data is determined to be valid, the CPU 62 signals the card reader 38 to lock the access card therein (step 210). The CPU 62 also signals the solenoid door lock 40 via the freezer interface 72 causing the solenoid door lock to disengage the door of the refrigeration unit 20 (step 212). With the door of the refrigeration unit 20 unlocked,

- 7 -

the user is able to open the refrigeration unit 20 thereby to gain access to supplies therein.

When the user opens the door of the refrigeration unit and the door light switch closes the circuit to illuminate the interior light within the refrigeration unit 20, a signal is conveyed to the CPU 62. The CPU 62 in turn generates a time stamp using the real-time clock allowing the time the refrigeration unit 20 is in an open condition to be accurately tracked. As the user begins removing items from the refrigeration unit 20, the tag on each removed item is detected by the internal sensor antenna. The internal sensor antenna in turn signals the CPU 62 via the communications interface 84 and databus 66 allowing the CPU 62 to maintain a count of the removed items (step 222).

When the door of the refrigeration unit 20 is closed, the CPU 62 conditions the barcode scanner 34 to a ready state and ends the time stamp (step 224). As a result, the length of time each user maintains the refrigeration unit 20 opened can be monitored. Extended door open conditions that may cause undesired temperature changes within the refrigeration unit 20 can also be detected. With the barcode scanner 34 enabled, the user is required to pass the removed items beneath the barcode scanner 34 so that the barcodes on the removed items can be scanned. After each barcode is scanned, the barcode scanner 34 conveys the scanned barcodes to the CPU 62 allowing the CPU 62 to maintain a list of the scanned removed items (step 226). When the counted scanned items is equal to the removed item count, the CPU 62 signals the solenoid door lock 40 via the freezer interface 72 causing the solenoid door lock 40 to engage the door of the refrigeration unit 20 (step 230). The access card is then ejected from the card reader 38 (step 208) and the card reader returns to a ready state waiting for another access card to be inserted therein (step 200). As will be appreciated, since a count of removed items is maintained and compared with the list of scanned barcodes, accurate transactions involving inventory within the refrigeration unit 20 can be maintained.

After a user has completed a transaction with the refrigeration unit 20, the CPU 62 conveys the scanned barcode information to a remote site over a wireless communication link via the radio interface 70 and one of the transceivers 74 or 76. In the scenario shown in Figure 10, the inventory-tracking unit 30 conveys the

- 8 -

transaction to a remote site 100 over a wireless wide area network 102 via radio interface 70 and WAN transceiver 74. In the scenario shown in Figure 12, inventory-tracking units 30 convey transactions to a computer room 104 over a wireless local area network 106 via radio interfaces 70 and LAN transceivers 76. database so that an accurate real-time status of the inventory within the refrigeration unit 20 can be maintained. The maintenance of accurate inventory information allows useful sales reports to be generated and allows replenishment schedules to be adjusted to conform to inventory demand. Generated reports are posted on encrypted web pages that can be accessed by authorized users via Internet connections.

Depending on the environment, the scanned barcode data may be used to debit an account associated with the user. In this case, when the debit value of the account reaches a threshold level, the remote site generates a request for funds to zero the debit value. In this manner, the access card functions as both an access and debit card i.e. similar to a smart card.

If at any time, the temperature within the refrigeration unit rises above the threshold temperature as detected by the thermistor, the internal sensor antenna in the refrigeration unit 20 signals the inventory-tracking unit 30. In response, the CPU 62 generates an alarm signal that is used to sound siren 56 and records the alarm event. The CPU 62 also conveys the alarm event to the remote site over the wireless communications link so that the alarm event is recorded. The CPU 62 also generates and records an alarm event when the door of the refrigeration unit 20 is left open for an extended period of time above a threshold and when the compressor of the refrigeration unit is believed to be approaching its service life. These alarm events are also recorded and conveyed to the remote site over the wireless communications link. In this manner service personnel can be quickly dispatched.

If desired, since the internal sensor antenna detects when items are placed into the refrigeration unit 20, the inventory-tracking unit 30 can be programmed to maintain an item count during restocking and convey the item count to the remote site providing for complete inventory control.

Figures 1 and 11 show a small number of inventory-tracking units 30 communicating with a remote site. Those of skill in the art will appreciate that this is

- 9 -

for illustrative purposes only. In a typical environment, remote site receives transactions from a significant number of geographically distributed inventory-tracking units 30. Also, the inventory-tracking units may be used with other types of storage units such as for example vending machines and the like. In the case of
5 vending machines that securely hold items, the requirement for a door locking mechanism is obviated.

Although preferred embodiments of the present invention have been described, those of skill in the art will appreciate that variations and modifications may be made without departing from the spirit and scope thereof as defined by the
10 appended claims.

- 10 -

What is claimed is:

1. An inventory-tracking unit associated with a storage unit holding items to be dispensed comprising:
 - 5 a card reader to read an access card issued to a user;
 - a scanner to scan data from items removed from said storage unit;
 - a processor communicating with a sensor in said storage unit and with said card reader and scanner, said sensor providing item data to said processor that is associated with items removed from said storage unit, said processor comparing item
 - 10 data received from said sensor with data received from said scanner to detect coincidence, said processor generating a transaction upon coincidence of item data received from said sensor with said scanned data; and
 - a communications interface to transmit said transaction to a remote site.
- 15 2. An inventory-tracking device according to claim 1 wherein said communications interface transmits said transaction over a wireless communications link.
- 20 3. An inventory-tracking device according to claim 2 wherein said scanner is a barcode scanner.
4. An inventory-tracking device according to claim 3 wherein said card reader is designed to read a magnetic stripe on said access card.
- 25 5. An inventory-tracking device according to claim 4 further including a housing accommodating said card reader, scanner, processor and communications interface, said housing being coupled to said storage unit and said processor being wired to said sensor.

30

- 11 -

6. An inventory-tracking device according to claim 5 wherein said card reader locks said access card therein until the item data received from said sensor is coincident with said read data.
- 5 7. An inventory-tracking unit according to claim 6 further comprising a locking mechanism coupled to said storage unit to inhibit access to items held therein, said locking mechanism being conditioned by said processor to a disengaged state to permit access to items held in said storage unit when a valid access card is read by said card reader.
- 10 8. An inventory-tracking unit according to claim 7 wherein said storage unit is a refrigeration unit storing medical supplies, said locking mechanism inhibiting a door of said refrigeration unit from being opened when in an engaged state.
- 15 9. An inventory-tracking unit according to claim 7 wherein said processor communicates with at least one diagnostic sensor associated with said storage unit, said processor transmitting an alarm event to said remote site in response to alarm condition input received from said at least one diagnostic sensor.
- 20 10. An inventory-tracking unit according to claim 9 wherein said storage unit is a refrigeration unit storing medical supplies, said locking mechanism inhibiting a door of said refrigeration unit from being opened when in an engaged state.
- 25 11. An inventory-tracking unit according to claim 10 wherein said at least one diagnostic sensor includes a temperature sensor to monitor the temperature within said refrigeration unit and generate said alarm condition input when the temperature within said refrigeration unit exceeds a threshold.
- 30 12. An inventory-tracking unit according to claim 9 wherein said storage unit is a vending machine.

Amendement au numéro de commande: 2430181

Figures: 7, 8, 10, 11, 12

Pages: _____

Unscannable items
received with this application
(Request original documents in File Prep. Section on the 10th floor)

Documents reçu avec cette demande ne pouvant être balayés
Commander les documents originaux dans la section de préparation des dossiers au
Même étage




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6

Fig. 9

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☒ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)